

QZ .049

0.819 cc

Muffler*
Equipped

Reed Valve Engine QUIET

WHISPER QUIET! DESIGNED FOR

NEIGHBORHOOD OPERATION

CAT. NO. 450

COMPANION OF WORLD FAMOUS COX BABE BEE .049

PAT. NO. 3132716 MADE IN U.S.A.

QZ .049 INSTRUCTIONS

TO START ENGINE

1. Close needle valve (do not tighten)
then open 2½ turns.

 Fill tank through either filler tube, on top of tank, with Cox Thimble Drome glow fuel.

 Move muffler spring so that a few drops of fuel can be dropped into cylinder exhaust ports. Flip propeller over

3 or 4 times.

4. Connect 1½ volt battery to glow head. Engage starter spring over prop, wind backwards 1 full turn — then release. Engine should start. If engine does not start repeat step 3. Note: NEVER wind starter spring more than 1½ turns.

After engine starts, close needle valve slowly until maximum RPM is reached.

Disconnect battery.

 Move muffler spring until it COM-PLETELY closes exhaust opening, Noise will then be suppressed.

RECOMMENDED PROPELLERS

862	6.	DIa.	X	3	PITCH	,45
858	5"	Dia.	X	3"	Pitch2/	.49
004	511	Dia	Y :	211 P	itch (3 hladed) 2/	10

FAILURE TO START

- Refuses to fire Weak or dead battery, bad wire connections or burned out glow plug — plug should glow red.
- Starts, slows down, stops excess fuel at ports. Close needle valve. Flip propeller till engine starts and burns out excess fuel. Open needle valve and restart.
- Engine starts with lots of power and dies — not getting fuel. Open needle valve another ½ turn and repeat starting procedure. If trouble persists, check for clogged fuel passages,
- Engine pops and fires, will not run dirt under reed. Carefully unsnap reed retainer — remove reed — wash in solvent or fuel — replace reed with same side out.

Send \$1.00 in with engine for any service. For charge in excess of \$1.00 you will be notified. Complete overhaul, new performance guaranteed \$3.50.

RTS LIST

PARIS LIST								
1702	GLOW HEAD	1230	WRENCH					
303	PISTON AND ROD1.50	351	CRANKCASE1.25					
7904	CYLINDER1.75	358	TANK BACK1.10					
365	CRANKSHAFT1.50	364	REED					
309	NEEDLE VALVE AND SPRING60	363	REED RETAINER					
352	PROPELLER DRIVE WASHER25	6223	PROP SCREW					
368	FUEL TANK WITH REED		MUFFLER ASSY1.50					
	ASSEMBLY1.00		SPRING STARTER					
354	SET OF GASKETS20		subject to change without notice.					
369	SCREWS	* Pat.	No. 2,927,660					

L. M. COX Manufacturing Company, Inc.

Mage in U.S.A. P.O. Box 476, Santa Ana, California